

MA14-A

SELF-PROPELLED ARTICULATED BOOMS

HELI

Product Highlights

- ★Electric drive, green and environmentally friendly
- ★Zero emissions, meeting the strict requirements of indoor and outdoor emissions on construction sites

Compact Structure

- ★The entire series adopts compact design, while also considering high maintenance, and has stronger ability to operate in narrow and complex working conditions.

Excellent Performance

- ★Equipped with a maximum working angle of 3 degrees as standard, the entire series have stronger adaptability to the working range and site.
- ★230kg load capacity, adaptable to multiple scenarios and working conditions

Low Maintenance Costs

- ★Compared to diesel power, battery maintenance costs are lower, reducing overall operating costs.

Electric Drive

- ★Low cost, low noise, low maintenance, green environmental friendly and energy conservation



Standard Features

Hydraulic leveling platform	Mechanical release of driving brake	Horn and buzzer safety warnings
Automotive grade full tube sheath protection	Platform rotation	Maximum tilt angle of 3°
Tilt alarm	Over Load sensor	Flash light
Emergency stop system	Emergency lowering system	Diagnosis system

Options Features

AC wiring to platform	T-BOX (GPS)
Non-marking solid tires	

Model	MA14-A
Dimension	
Max. Working Height	16m
Max. Platform Height	14m
Max. Outreach	8.22/8.32m
Max. Up and Over Clearance	6.92/7.47m
A Length (stowed)	5.88/6.47m
B Width (stowed)	1.75m
C Height (stowed)	2m
D Wheelbase	2m
Ground Clearance	0.14m
Platform Size	1.5×0.76×1.1m
Performance	
Lift Capacity	230kg
Turntable Rotation	360°non-continuous
Platform Rotation	180°
Drive Speed (Stowed)	4.8km/h
Drive Speed (Raised)	1km/h
Gradeability	30%
Turning Radius (Inside)	1.1m
Turning Radius (Outside)	3.5m
Turntable Tailswing	0
Max. Tilt Angle(front to back/side to side)	5°/3°
Drive wheels number x Steering wheels number	2×2
Tire Specification/ Type	600*190(solid tire)
Power	
Battery Specifications	DC48/320Ah
Voltage	DC24V
Hydraulic Tank Capacity	35L
Weight	
Total Weight	6490/6640kg

